



REDLUBE PREMIUM HD 15W-40

DESCRIPTION

The high-quality, multigrade engine oil **REDLUBE PREMIUM HD 15W-40** is perfect for diesel engines running constantly in difficult circumstances. It is appropriate for turbocharged and direct-injected engines in environments with high levels of engine stress.

ADVANTAGES

REDLUBE PREMIUM HD 15W-40 offers the following advantages:

- Better engine protection for essential engine components.
- Outstanding cleaning, even at prolonged drain interval times.
- Superior engine protection
- Excellent engine performance and decreased deposits.
- Effectively neutralizes the corrosive combustion acids while safeguarding the engine components.
- Its highly efficient and durable synthetic formulation minimizes friction and improves engine performance.
- Prolonged Drain Period

SPECIFICATIONS & APPROVALS

REDLUBE PREMIUM HD 15W-40 satisfies or surpasses the following performance criteria:

- API CI-4 Plus
- API CI-4 Plus/CI-4/ CH-4



TECHNICAL SPECIFICATIONS

REDLUBE PREMIUM HD 15W-40

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 3.5
Density @ 29.5°C, gm/cc	D4052	0.885
Kinematic Viscosity @ 40°C, cSt	D445	106
Kinematic Viscosity @ 100°C, cSt	D445	14.52
Viscosity Index	D2270	137
Flash Point, °C	D92	228
Pour Point, °C	D97	-33
Total Base Number, mg KOH/gm	D2896	12
CCS Viscosity @ -20°C, cP	D5293	6820

Material on this page could change at any time without prior notice. Neither we nor the manufacturers are responsible for any loss or damage, regardless of how it may have been caused by using such information.

ENVIRONMENT, HEALTH AND SAFETY

Avoid disposing of used oil in the ground, sewers, or water. Dispose of used oil at a designated collecting location. This product is not expected to produce adverse health effects if used for intended application with proper safety procedures. Please avoid prolonged skin contact with all types of motor oil. Wash with water and soap after any skin contact.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container inclosed condition always.