



REDLUBE SUPER 4T 20W-50

DESCRIPTION

REDLUBE SUPER 4T 20W-50 is an advanced 4T engine oil created especially for modern day four stroke engines. Made up of highly refined premium minerals and the latest additive system, **REDLUBE SUPER 4T 20W-50** ensures quick and steady flow of the lubricant throughout the engine which helps reduce cold start wear and tear. It remains viscous in high temperature and provides maximum performance under extreme pressure.

FEATURES AND BENEFITS

Features	Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components
Broad viscosity range	Year-round engine protection and performance

SPECIFICATIONS & APPROVALS

REDLUBE SUPER 4T 20W-50 satisfies or surpasses the following performance criteria:

- API SL/SJ/SG
- JASO MA2

ADVANTAGES

REDLUBE SUPER 4T 20W-50 offers the following advantages:

- Longer Engine Life
- Reduced Oil Consumption
- Perfect Lubrication & Power



TECHNICAL SPECIFICATIONS

REDLUBE SUPER 4T 20W-50

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 3.0
Density @ 29.5°C, gm/cc	D4052	0.89
Kinematic Viscosity @ 40°C, cSt	D445	185
Kinematic Viscosity @ 100°C, cSt	D445	20.5
Viscosity Index	D2270	118
Flash Point, °C	D92	230
Pour Point, °C	D97	- 33
Total Base Number, mg KOH/gm	D2896	7.41
CCS Viscosity @ -15°C, cP	D5293	7700

Manufacturers do not assume responsibility for any loss or harm, however, resulting from the use of their suggestions and recommendations, which are provided "as is." Manufacturers disclaim any responsibility for any claims or representations made in this article, and information is subject to change without notice.

ENVIRONMENT, HEALTH AND SAFETY

Avoid disposing of used oil in the ground, sewers, or water. Dispose of used oil at a designated collecting location. This product is not expected to produce adverse health effects if used for intended application with proper safety procedures. Please avoid prolonged skin contact with all types of motor oil. Wash with water and soap after any skin contact.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition

always.