



REDLUBE TITAN POWER 10W-30

DESCRIPTION

REDLUBE TITAN POWER 10W-30 is a newly introduced engine oil for four-stroke motorcycles. Its Advanced Cleaning Technology (ACT) ensures exceptional engine performance which results into longer engine life and greater engine protection.

APPLICATIONS

REDLUBE TITAN POWER 10W-30 is recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Normal to occasionally severe operating conditions
- Performance engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your vehicle.

SPECIFICATIONS & APPROVALS

REDLUBE TITAN POWER 10W-30 satisfies or surpasses the following performance criteria:

- API SN

ADVANTAGES

REDLUBE TITAN POWER 10W-30 has the following benefits:

- Longer engine life.
- High fuel efficiency
- Superior Engine Cleanliness
- Optimum Engine Protection in Tough Conditions.

TECHNICAL SPECIFICATIONS

REDLUBE RACING 4T 10W-40

PROPERTIES	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Bright & Clear
Color	ASTM D1500	L 2.5
Density @ 29.5 °C, gm/cc	ASTM D4052	0.8500
Kin. Viscosity @ 40 °C, cSt	ASTM D445	61.00
Kin. Viscosity @ 100 °C, cSt	ASTM D445	10.10
Viscosity Index	ASTM D2270	153
Flash Point, COC, °C	ASTM D92	240
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/gm	ASTM 2896	7.10
CCS Viscosity @ -25 °C, cP	ASTM D5293	4300

Material on this page could change at any time without prior notice. Neither we nor the manufacturers are responsible for any loss or damage, regardless of how it may have been caused by using such information.

ENVIRONMENT, HEALTH AND SAFETY

Avoid disposing of used oil in the ground, sewers, or water. Dispose of used oil at a designated collecting location. This product is not expected to produce adverse health effects if used for intended application with proper safety procedures. Please avoid prolonged skin contact with all types of motor oil. Wash with water and soap after any skin contact.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.