



REDLUBE ULTRA 4T 10W-30

DESCRIPTION

REDLUBE ULTRA 4T 10W-30 is a high performance four-stroke engine oil, specially designed for modern engine technology keeping development trends led by major OEMs in consideration. **REDLUBE ULTRA 4T 10W-30** combines the latest technology with the most recent API SL advanced additive technology. To prolong the life of the engine and increase fuel efficiency, it offers 57% greater wear protection. To stop engine wear, heat-activated anti-wear molecule helps keep the viscosity of the oil at high temperatures.

FEATURES AND BENEFITS

- Ability to remain highly viscous in high temperatures help provide maximum performance under extreme pressure.
- **EST** ensures quick and steady flow of lubricant throughout the entire engine which help maximize performance.
- Anti-wear molecules help reduce engine wear and tear, and prevents cold start wear.
- Advanced formulation for performance in extreme conditions

SPECIFICATIONS & APPROVALS

REDLUBE ULTRA 4T 10W-30 satisfies or surpasses the following performance criteria:

- API SL/SJ/SG
- JASO MA2

ADVANTAGES

REDLUBE ULTRA 4T 10W-30 offers the following advantages:

- Clutch Friction Control
- Excellent Engine Cleanliness
- Longer Oil Drain Interval



TECHNICAL SPECIFICATIONS

REDLUBE ULTRA 4T 10W-30

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES
Appearance	Visual	Clear & Bright
Colour ASTM	D1500	L 2.5
Density @ 15 C, g/ml, ASTM	D1298	0.866
Kinematic Viscosity @ 40°C, cSt	D445	69.00
Kinematic Viscosity @ 100°C, cSt	D445	10.5
Viscosity Index	D2270	140
Flash Point, °C	D92	230
Pour Point, °C	D97	-33
Total Base Number, mg KOH/gm	D2896	5.8
CCS Viscosity @ -25°C, cP	D5293	6163

Material on this page could change at any time without prior notice. Neither we nor the manufacturers are responsible for any loss or damage, regardless of how it may have been caused by using such information.

ENVORNMENT, HEALTH AND SAFTEY

Avoid disposing of used oil in the ground, sewers, or water. Dispose of used oil at a designated collecting location. This product is not expected to produce adverse health effects if used for intended application with proper safety procedures. Please avoid prolonged skin contact with all types of motor oil. Wash with water and soap after any skin contact.

STORAGE

Store the products indoors and avoid direct sunlight or heat. Please keep the container in closed condition always.